



US005805816A

United States Patent [19]
Picazo, Jr. et al.

[11] **Patent Number:** **5,805,816**
[45] **Date of Patent:** **Sep. 8, 1998**

[54] **NETWORK PACKET SWITCH USING SHARED MEMORY FOR REPEATING AND BRIDGING PACKETS AT MEDIA RATE**

5,440,690 8/1995 Rage et al. 395/200.8
5,457,681 10/1995 Gaddis et al. 370/56
5,477,547 12/1995 Sugiyama 370/85
5,521,913 5/1996 Gridley 370/58.2
5,560,029 9/1996 Papadopoulos et al. 395/800.25

[75] Inventors: **Jose J. Picazo, Jr.**, San Jose; **Paul Kakul Lee**, Union City; **Robert P. Zager**, San Jose, all of Calif.

Primary Examiner—Christopher B. Shin
Attorney, Agent, or Firm—Jenkins & Gilchrist

[73] Assignee: **Compaq Computer Corp.**, Houston, Tex.

[57] **ABSTRACT**

[21] Appl. No.: **788,429**

[22] Filed: **Jan. 28, 1997**

Related U.S. Application Data

[62] Division of Ser. No. 694,491, Aug. 7, 1996, which is a continuation of Ser. No. 498,116, Jul. 5, 1995, which is a continuation-in-part of Ser. No. 881,931, May 12, 1992, Pat. No. 5,432,907.

[51] **Int. Cl.**⁶ **G06F 13/00**

[52] **U.S. Cl.** **395/200.53; 395/200.64; 395/200.79; 395/200.8; 370/401; 370/230; 370/315; 370/351**

[58] **Field of Search** **395/200.53, 200.64, 395/200.79, 200.8; 370/230, 315, 351, 401**

[56] **References Cited**

U.S. PATENT DOCUMENTS

4,641,307	2/1987	Russell	370/445
4,715,030	12/1987	Koch et al.	370/85
5,133,062	7/1992	Joshi et al.	395/500
5,210,749	5/1993	Firoozmand	370/463
5,264,742	11/1993	Sourgen	307/465
5,274,631	12/1993	Bhardwaj	370/401
5,299,313	3/1994	Petersen et al.	395/200.64
5,303,302	4/1994	Burrows	380/49
5,339,313	8/1994	Ben-Michael et al.	370/230
5,361,372	11/1994	Rege et al.	395/200.64
5,434,863	7/1995	Onishi et al.	395/200.64
5,440,546	8/1995	Bianchini, Jr. et al.	370/60

A hub circuit with an integrated bridge circuit carried out in software including a switch for bypassing the bridge process such that the two bridged networks effectively become one network. An in-band management process in software is disclosed which receives and executes network management commands received as data packets from the LANs coupled to the integrated hub/bridge. Also, hardware and software to implement an isolate mode where data packets which would ordinarily be transferred by the bridge process are not transferred except in-band management packets are transferred to the in-band management process regardless of which network from which they arrived. Also disclosed, a packet switching machine having shared high-speed memory with multiple ports, one port coupled to a plurality of LAN controller chips coupled to individual LAN segments and an Ethernet microprocessor that sets up and manages a receive buffer for storing received packets and transferring pointers thereto to a main processor. The main processor is coupled to another port of the memory and analyzes received packets for bridging to other LAN segments or forwarding to an SNMP agent. The main microprocessor and the Ethernet processor coordinate to manage the utilization of storage locations in the shared memory. Another port is coupled to an uplink interface to higher speed backbone media such as FDDI, ATM etc. Speeds up to media rate are achieved by only moving pointers to packets around in memory as opposed to the data of the packets itself. A double password security feature is also implemented in some embodiments to prevent accidental or intentional tampering with system configuration settings.

6 Claims, 13 Drawing Sheets

